



# enerflex.

raising the standards



POWER SUPPLIES



1202SM-1



1202SM-1



**SPECIFICATION**

- Full current to load
- 12-14VDC adjustable voltage output
- Additional battery charging
- Deep discharge protection
- Current limiting
- Short circuit protection
- 230V fused input
- Mains transient protection
- Compliant to EMC EN61000-6-1 & 3
- **Up to 92% energy efficiency (reduced running costs and lower power usage)**

Available in the following models as standard:  
 1201SM-1 / 1201SM-2 / 1202SM-1 / 1202SM-2  
 1203SM-1 / 1203SM-2 / 1205SM-1 / 1205SM-2  
 12TENS-2

**FEATURES**

- Switchmode technology
- Din rail design for greater versatility
- Mild steel construction
- White powder coated
- LED Indicators (mains, batt, output)
- Separate fused main connectors
- Full electronic protection
- Onboard tamper protection
- Converts power more efficiently
- Multiple cable entry
- Allows for 1 x 7/9Ah batteries (SM-1)

Utilising market leading Gallium Nitride technology (GaN)


**OTHER PRODUCTS**



IPBOX-2



VP-EEB



TLI-45

**DIMENSIONS**

- SM-1
- 225H x 196W x 75D (mm)
  - 1.46kg (Boxed) • 1.32kg (Unboxed)
- SM-2
- 310H x 340W x 80D (mm)
  - 3.07Kg Boxed • 2.84Kg Unboxed

**CONTENTS**

- Power Supply Unit
- 2 x Battery Leads (1 x Red, 1 x Black)
- 1 x Earth Lead - Connected
- Wiring instructions included



Manufactured by a BSIA Member

CDL-300

