LATCHING KEY SWTICH

KS-1

SPECIFICATION

KS-1
• Latching on/off operation
• Key removal in both positions
• Keyed alike
• Supplied with 2 x keys (2803)
• Voltage free contacts
• NONC contacts > 1 million operations
• Rated IP54 ingress protection
• Etched legend (ON - OFF)
• Security screws

FEATURES

KS-1
• Functional design
• Easy to operate
• Use for secure override
• Easy clean surface (ideal for hospitals/public areas)
• Screw footprint for surface fitting onto standard back box
• Footprint for mounting onto flush back box

ALTERNATIVES
• KS-2 (Momentary Operation)
• KS-3 (3 Position Key Switch)
• JMB/KS-1 (Latching Key Switch in Jamb Box)
• JMB/KS-3 (3 Position Key Switch in Jamb Box)
• WP-KS-1 or 2 (Weatherproof Key Switch)
• EXT/AP/KS-1 or 3 (Architrave Extrusions KS)

OTHER PRODUCTS

WP-KS-1

EXT/AP/KS-1

JMB/KS-1

EXT/AP/KS-3

DIMENSIONS

KS-1
• 85x85x50/40 (mm) (HxWxD)
• 260g (Boxed)
• 212g (Unboxed)

CONTENTS

KS-1
• Key Switch
• Stainless Steel Plate (2mm)
• 2 x Keys (2803)
• 2 Security Screws
• Allen Key
• Shrouded Surface Box

LRQA CERTIFIED ISO 9001

UKAS MANAGEMENT SYSTEMS 0001

bsia british security industry association
Manufactured by a BSIA Member