

ARCHITECTURAL DOOR HANDLE RANGE





SPECIFICATION

DHM600, DHM600-60 + DHM600-200

- · Aluminium housing
- · 12/24VDC @ 450/265mA
- ·1 x 280kg (600lb) holding force
- · Built in surge protection
- · Monitored (door open or door closed detection)
- · Suitable for all inward opening wooden or aluminium doors
- · Delay timer 0/2.5/5/9 seconds
- · Built in exit button (Optional)
- · Visible LED indication

DHM600-60 + DHM600-200

- · 12/24VDC @ 920/460mA
- · 2 x 280kg (600lb) holding force

FEATURES

DHM600

DHM600, DHM600-60 + DHM600-200

- · Slimline monitored magnet
- · Built in exit button (Optional)
- · Built in timer delay
- · No residual magnetism
- · Install at centre of door leaf to prevent distortion

OTHER PRODUCTS

EDR-N





DIMENSIONS

DHM600

300 x 92 x 58mm / 274 x 46.2 x 30mm 3kg

DHM600-60

600 x 92 x 58mm /575 x 46.2 x 30mm 6kg

DHM600-200

1980 x 92 x 58mm / 1955 x 46.2 x 30mm 13.5kg



CONTENTS

DHM600, DHM600-60 + DHM600-200

- · Magnetic Lock
- · Door Handle with built in armatures

- · Fixing Kit
- Fixing template





