



TOUCH FREE EXIT DEVICE

HELPS STOP THE SPREAD OF GERMS

EXIT BUTTONS

Market leading request to exit buttons, that are both hard wearing and cost effective. Suitable for use in applications where contactless options are a priority.



K-EB/TF-DR



K-EB/AP/TF-DR

SPECIFICATION

- K-EB/TF-DR & K-EB/AP/TF-DR
- Contacts: Double pole NONC contacts
 - Contact Load: 0.5A @ AC 120V / 1A @ DC24V
 - Dual voltage 12/24 VDC @ 45mA operating
 - +/- 10% voltage tolerance
 - Etched legend (DOOR RELEASE)
 - Security screws (allen key type)
 - Button rated IP65 ingress protection
 - Adjustable relay opening times (0.5 to 20 sec)
 - Adjustable proximity distance (3 to 12 cm)
 - -10° to +70° operating temperature
 - Designed to prevent interference with other infra red devices

Requires a permanent power supply
- volt free contacts

DIMENSIONS

- K-EB/TF-DR & K-EB/AP/TF-DR
- 85x85x35 (mm) / 85x39x40 (mm)
 - 238g (Boxed)
 - 202g (Unboxed)

FEATURES

- K-EB/TF-DR & K-EB/AP/TF-DR
- 38mm / 22mm Touch free sensor button
 - Illumination - Green to red (or red to green)
 - Flush mounted box
 - Can be surface fitting with EXTR03 or EXTR04
 - Easy clean surface
 - Ideal for general / sensitive areas
 - Screw footprint for flush fitting onto standard back box
 - Distance between fixing holes 60mm

- Suitable Alternative Back Boxes
- EXTR03 (Aluminium Extrusion 40mm)
 - SSBB02 (Stainless Steel Back Box 42mm)
 - PBB05 (Green Back Box 40mm)
 - EXTR04 (45mm Extrusion for Narrow Version)

CONTENTS

- K-EB/TF-DR & K-EB/AP/TF-DR
- Touch free button on SS Plate
 - Flush back box
 - Wires & connector
 - Screw bag
 - Instructions

OTHER PRODUCTS

MED-57K



1205SM



SPX-26M



IPBOX-5



Manufactured by a BSIA Member