



SELF RESETTING EXIT BUTTON

EXIT BUTTONS

Market leading manufacturer making a wide range of exit devices, relays and modules to suit a plethora of requirements.



SREB/YB

SPECIFICATION	FEATURES	OTHER PRODUCTS
---------------	----------	----------------


SREB/YA

- Flush fitting
- Stainless steel plate
- IP65 rated switch
- Output: 4 AMP contact @ 30V AC/DC
- Double pole NO/NC contact
- Both contacts can be installed to provide a fail safe solution
- Use normally open circuit to trigger a timed exit on controller (Normally closed circuit will remove power to lock directly on a momentary basis)
- Can be used to replace a green break glass that is often misused (must be approved by local fire control)

SREB/YB

- Stainless Steel Button
- Momentary operation / contact
- Flush fitting as standard
- Easy clean surface
- Ideal for general / sensitive areas
- Gasket and gland included
- Screw footprint for flush fitting onto standard back box
- Distance between fixing holes 60mm
- Yellow halo to assist visually impaired users

TLI-85



IPBOX-2



DIMENSIONS	CONTENTS
------------	----------

SREB/YB

- 85x85 (mm)
- 220g (Boxed)
- 178g (Unboxed)

SREB/YB

- Stainless Steel Exit Button
- Stainless Steel Plate (2mm)
- 2 Security Screws
- Allen Key
- Electrical back box
- Instructions

MED-57



SPX-26M

