



# WEATHERPROOF EXIT BUTTON

# EXIT BUTTONS



**WP66-G-GB/PTO**



**WP66-G-GB/GR**



**WP66-Y-RB/PA**



Market leading door release button, that is both hard wearing and cost effective. Suitable for use in applications up to 30V.

SPECIFICATION	FEATURES	OTHER PRODUCTS
---------------	----------	----------------

WP66

- Contacts: Double pole N/O - N/C
- Output: 4 AMP contact @ 30V AC/DC
- Wear resistant legend (others available on request)
- External use
- IP66 ingress protection (button & enclosure)
- Robust two part cross polymer housing
- M16/20 pre moulded conduit knockouts
- Silver contacts
- Operating temperature -20° to +60°c
- Operating travel: 2mm
- Contact resistance: 10m OHM (Max)
- Operating life (mechanical): 1,000,000

WP66

- Large plastic green/red button
- Momentary operation / contact
- High impact plastic back box
- Surface fitting
- Easy clean surface.
- Ideal for general/sensitive areas
- IP66 weatherproof unit

Any variations of the above switches are available.



DIMENSIONS	CONTENTS
------------	----------

WP66

- 85H x 90W x 60/80D (mm)
- 248g (Boxed)
- 200g (Unboxed)

WP66

- Green/Red/Blue Dome Exit Button
- 4 Screws
- Surface Enclosure



Manufactured by a BSIA Member