







WEATHERPROOF EXIT BUTTON

EXIT BUTTONS

Market leading stainless steel button, that is both hard wearing and cost effective. Suitable for use in applications up to 30V.



WP66-G-SS/PTE

SPECIFICATION	FEATURES	OTHER PRODUCTS
<p>WP66-G-SS/PTE</p> <ul style="list-style-type: none"> • Contacts: Double pole N/O - N/C • Output: 4 AMP contact @ 30V AC/DC • Wear resistant legend (others available on request) • External use • Button rated at IP65 • Enclosure rated at IP66 • Robust two part cross polymer housing • M16/20 pre moulded conduit knockouts • Silver contacts • Operating temperature -20° to +60°c • Operating travel: 2mm • Contact resistance: 10m OHM (Max) • Operating life (mechanical): 1,000,000 	<p>WP66-G-SS/PTE</p> <ul style="list-style-type: none"> • Stainless Steel Button • Momentary operation / contact • High impact plastic back box • Surface fitting • Easy clean surface • Ideal for general / sensitive areas • IP66 weatherproof unit <p>Alternative Legends Available:</p> <ul style="list-style-type: none"> • PUSH TO OPEN • GATE RELEASE • DOOR RELEASE 	<p>EBNT/TF-IPLUS</p>  <p>AH600</p> 
<p>DIMENSIONS</p> <p>WP66-G-SS/PTE</p> <ul style="list-style-type: none"> • 85H x 90W x 60/80D (mm) • 248g (Boxed) • 200g (Unboxed) 	<p>CONTENTS</p> <p>WP66-G-SS/PTE</p> <ul style="list-style-type: none"> • Stainless Steel Exit Button • 4 Screws • Surface Enclosure 	<p>ML600</p>  <p>JMB/KS-1</p> 



Manufactured by a BSIA Member