



WEATHERPROOF EXIT BUTTON

EXIT BUTTONS

Market leading illuminated button, that is both hard wearing and cost effective. Suitable for use in applications up to 30V.



WP66-G-ILG/PTO



WP66-G-ILG/GR



WP66-Y-ILB/PFA

SPECIFICATION	FEATURES	OTHER PRODUCTS
---------------	----------	----------------

WP66

- Contacts: NO/COM
- Contact rating: 500mA @24V AC/DC
- Voltage: 12-24VDC
- Wear resistant legend (others available on request)
- Button is rated at IP68
- IP66 ingress protection (enclosure)
- Robust two part cross polymer housing
- M16/20 pre moulded conduit knockouts
- Silver contacts
- Operating temperature -20° to +60°c
- Operating travel: 2mm
- Contact resistance: <50mΩ
- Operating life (mechanical): 1,000,000

WP66

- LED status:
 - Red / Green / Blue or Yellow (Static)
- Momentary operation / contact
- High impact plastic back box
- Surface fitting
- Easy clean surface.
- IP66 weatherproof unit

Any variations of the above switches are available.

Alternative Legends Available:
 PRESS TO EXIT (Green)
 DOOR RELEASE (Green)
 EMERGENCY STOP (Red)
 PANIC ALARM (Red)
 POOL ALARM (Blue)



DIMENSIONS

WP66

- 85H x 90W x 60/80D (mm)
- 248g (Boxed)
- 200g (Unboxed)

CONTENTS

WP66

- Red / Green / Blue or Yellow Illuminated Switch
- 4 Screws
- Surface Enclosure



Manufactured by a BSIA Member