

Market leading door release button, that is both hard wearing and cost effective. Suitable for use in applications up to 30V.

WEATHERPROOF EXIT BUTTON

TWIST OPEN







WP66-Y-TTO/ES

SPECIFICATION

WP66

- · Contacts: Double pole N/O N/C
- Output: 3 AMP contact @ 240V AC (2AMP @12/24VDC)
- Wear resistant legend (others available on request)
- External use
- · IP66 ingress protection (button & enclosure)
- · Robust two part cross polymer housing
- · M16/20 pre moulded conduit knockouts
- · Operating temperature -20° to +60°c

FEATURES

WP66

- Momentary operation / contact
- · High impact plastic back box
- · Surface fitting
- · Easy clean surface.
- · Ideal for general/sensitive areas
- · IP66 weatherproof unit

Any variations of the above switches are available, including switching to a grey back box.

OTHER PRODUCTS

EXML600-GATE



WP66-Y-ILB/PFA



DU-GB/PTE



DIMENSIONS

WP66

- · 85H x 90W x 60/80D (mm)
- · 248g (Boxed)
- · 200g (Unboxed)

CONTENTS

WP66

- · Red Latching Button
- · 4 Screws
- Surface Enclosure(2 x Keys with KR version)







+44 (0)1902 656667 | www.rgl.co | info@rgl.co